

## JuiceBox® 40

**Residential Charging Stations** 



# Charge forward with the best-selling smart home charging station

JuiceBox 40, the best-selling smart home charging station, combines speed, performance and value. Enjoyed by thousands of satisfied EV drivers, it delivers all the safety and smart charging features you need to make home charging easy, reliable and cost-effective.

JuiceBox is the only line of charging stations that affords both direct user control and smart grid optimization, accessible through the Enel X Way App.

- · Control charging anywhere, anytime via our mobile app
- Reduce your energy costs by scheduling charging when rates are low
- Select a cleaner electricity mix to reduce your emissions (in applicable geographies)
- Participate in smart grid programs to further lower the cost of owning and driving your EV (in applicable geographies)



### Why JuiceBox?

#### **Up to 7x Faster Charging**

Spend less time waiting for your EV to charge and more time enjoying the drive

#### **Powered by Enel X Way App**

Monitor and schedule charging with intuitive mobile app to save time and money

#### Easy to Use and Install

Small, lightweight enclosure; lockable, quick-release mount; weatherproof for indoor/outdoor installation

#### **Universal Compatibility**

SAE-J1772TM plug ensures compatibility with all EVs\*

#### **Cleaner Driving**

Optimize charging times and participate in smart grid programs to reduce emissions; ENERGY STAR®-certified

#### **See Charger Status**

Dynamic LED lights display WiFi connectivity and charging behavior

<sup>\*</sup>Tesla requires adapter



	0.6 III/17.3 CITI
JuiceBox 40 Specifica	ations enel *way
Electrical Characteristics	> Safety Rated: 40A Max
	> Single phase input: nominal voltage 110-240 VAC ~60 Hz
	> Power: 4.4 kW at 110 VAC; 9.6 kW at 240 VAC
Input Cable & Plug	> 2 ft/0.6 m with NEMA 14-50 and
	NEMA 6-50 plug options
	> 2.5 ft/0.8 m hardwire pigtail
Output Cable & Connector	> 25 ft/7.6 m cable
	> J1772 standard compliant
Enel X Way App	> Precision measurement of power, energy, voltage & current
	<ul> <li>Automated notifications: time-of-use in effect, start of charge, end of charge, unit offline,</li> </ul>
	unit back online, car not plugged in by a set time
	> See Enel X Way App Data Sheet for more on convenient features
Smart Grid Connectivity	> Built-in WiFi connectivity (802.11 b/g/n 2.4 GHz)
Firmware	> End-to-end AES-256-based encrypted protocols
	> 90-day, 15-minute interval data storage
	Over-the-air (OTA) upgradeable firmware
	Persistent data storage upon power interruption
<b>Emissions Reduction</b>	> Available via optional JuiceNet® Green software upgrade
Enclosure	> Dynamic LED lights show charging status: network connectivity, charging in progress,
	delaying charging, standby, charge complete/EV not drawing power
	> IP66: Weatherproof, dust-tight
	> IK10: Resistant polycarbonate case
	Quick-release wall mounting bracket included
	Built-in security lock and integrated cable management
	> Operating Temperature: -40°F to 140°F (-40°C to 60°C)
Altitude	) Up to 2000 m/6500 ft
Weight & Dimensions	Main enclosure: H: 18.5 in/469 mm x W: 6.8 in/173 mm x D: 5.8 in/147 mm
	> 15 lbs/6.8 kg
Codes & Standards	FCC Part 15 Class B, NEC 625 compliant, OCPP 1.6J, ENERGY STAR®
	> OpenADR 2.0b compliant
Safety	> UL and cUL Listed
Warranty	3-year limited product warranty (parts only) for use under normal residential operating conditions
Made in North America	> From domestic & imported parts

JUICEBOX and Enel X Way App are registered trademarks of Enel X North America, an Enel Group company. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.



6.8 in/17.3 cm

